

LOAD CHART

(48 UNITS = 1 FULL TRUCKLOAD)

C900 DR18/DR14/DR25

SIZE (")	DESCRIPTION	PCS/PAL	FT/PAL 20'	ORDER UNIT 20'	FT/TRUCK
4	DR 14/18/25	36	720	2.4	14400
6	DR 14	18	360	2.4	6840
6	DR 18/25	18	360	2.4	7200
8	DR 14/18/25	10	200	2.4	4000
10	DR 14/18/25	4	80	1.7	2560
12	DR 14/18/25	3 & 4	60/80	4	1960
14	DR18 / DR25	3	60	2	1440
16	DR18 / DR25	2 & 3	40/60	4.8	1000
18	DR18 / DR25	2 & 3	40/60	6	800
20	DR18 / DR25	2	40	3	640
24	DR18 / DR25	2	40	3	540

SEWER/DRAIN (SOLID, PERF) 3034 BE, GASKETED SEWER

SIZE (")	DESCRIPTION	PCS/PAL	FT/PAL 14'	ORDER UNIT 14'	FT/PAL 20'	ORDER UNIT 20'	FT/TRUCK 14'	FT/TRUCK 20'
3	D2729 S/D BE 10'	156	-	-	-	-	-	-
4	D2729 S/D BE 10'	90	-	-	-	-	-	-
6	D2729 S/D BE 10'	33	-	-	-	-	-	-
4	D3034 BE 10' & 20'	90	-	-	1800	4	-	-
6	D3034 BE 10' & 20'	33	-	-	660	4	-	-
4	D3034 GASKET	90	1260	2.67	1880	4	22680	21600
6	D3034 GASKET	40	560	2.67	800	4	10080	9600
8	D3034 GASKET	24	336	2.67	480	4	6048	5760
10	D3034 GASKET	12	168	2.67	240	4	3024	2880
12	D3034 GASKET	8	112	2	160	4	2688	2560
15	D3034 GASKET	3	42	1.33	60	4	1512	1440
18	F679 GASKET	3 & 2	42 & 48	3.2	-	-	1050	-
21	F679 GASKET	2	28	2	-	-	672	-
24	F679 GASKET	2	28	2	-	-	672	-
8	DR18 GREEN 14'	10	140	1.7	-	-	4200	-
10	DR18 GREEN 14'	4	56	1.18	-	-	-	-
12	DR18 GREEN 14'	7	98	2.8	-	-	-	-

* ALL D2729 AND D3034 BE 10' SEWER PALLETS ARE 2 ORDER UNITS

PRESSURE PIPE, WELL CASING, DWV

SIZE (")	DESCRIPTION	PCS/PAL	FT/PAL 20'	ORDER UNIT 20'	FT/TRUCK
1/2	SDR 13.5 315 PSI	480	9600	1	
1/2	SCH 40	480	9600	1	
1/2	SCH 80	480	9600	1	
3/4	SDR 21 200 PSI	300	6000	1	
3/4	SCH 40	300	6000	1	
3/4	SCH 80	270	5400	1	
1	SDR 21 200 PSI	400	8000	2	
1	SCH 40	200	4000	1	
1	SCH 80	200	4000	1	
1 1/4	SDR 26 160 PSI	281	5620	2	
1 1/4	SDR 21 200 PSI	281	5620	2	
1 1/4	SCH 40	281	5620	2	
1 1/4	SCH 80	138	2760	1	
1 1/2	SDR 26 160 PSI	203	4060	2	
1 1/2	SDR 21 200 PSI	203	4060	2	
1 1/2	SCH 40	203	4060	2	
1 1/2	SCH 80	94	1880	1	
2	SDR 26 160 PSI	140	2800	2	
2	SDR 21 200 PSI	140	2800	2	
2	SCH 40	140	2800	2	
2	SCH 80	140	2800	2	
2 1/2	SDR 26 160 PSI	87	1740	2	
2 1/2	SDR 21 200 PSI	87	1740	2	
2 1/2	SCH 40	87	1740	2	
2 1/2	SCH 80	87	1740	2	
3	SDR 26 160 PSI	60	1200	2	
3	SDR 21 200 PSI	60	1200	2	
3	SCH 40	60	1200	2	
3	SCH 80	60	1200	2	
4	SDR 26 160 PSI	36	720	2	17280
4	SDR 21 200 PSI	36	720	2	17280
4	SCH 40	36	720	2	17280
4	SCH 80	36	720	2	17280
4 1/2	SDR 26 160 PSI	24	480	2	11520
4 1/2	SCH 40	24	480	2	11520
4 1/2	SDR 17 250 PSI	24	480	2	11520
5	SDR 26 160 PSI	21	420	2	10080
5	SDR 17 20+	21	420	2	10080
5	SCH 40 / SDR 21	21	420	2	10080
5	SCH 80	21	420	2	10080
6	SDR 26 160 PSI	30	600	4	7200
6	SDR 17 250 PSI	30	600	4	7200
6	SDR 21 200 PSI	30	600	4	7200
6	SCH 40	30	600	4	7200
6	SCH 80	18	360	2.4	7200
6	SDR 17 Titeloc & TL SLOT	18	360	2.4	7200
6	Sch 40 TLC 20+	18	360	2.4	7200
6 1/2	SDR 21 200 PSI	18	360	2.4	7200
6 1/4	SDR 27.6 20+	18	360	2.4	7200
8	SCH 40/SDR 26 160 PSI	18	360	4	4320
8	SDR 21 200 PSI	18	360	4	4320
8	SCH 40 PE	18	360	4	4320
8	SCH 80	9	180	2	4320
10	SDR 26 20+	11	220	4	2640
10	SDR 21 20+	11	220	4	2640
10	SCH 40 PE & BE	11	220	4	2640
12	SDR 26 20+	4	80	2*	2240
12	SDR 21 20+	4	80	2*	2240
12	SCH 40 PE & BE	4	80	2*	2240
16	SCH 40 20+	6	120	4	1440
16	SDR 26 20+	6	120	4	1440
16	SCH 40 SLOT	3	60	2	1440